UTAH OIL AND GAS CONSERVATION COMMISSION SUB. REPORT/abd REMARKS WELL LOG ELECTRIC LOGS WATER SANDS LOCATION INSPECTED __Oil FILE_ 5-18-81 DATE FILED U-40560 A STATE LEASE NO. PUBLIC LEASE NO LAND: FEE & PATENTED INDIAN 10-20-81 DRILLING APPROVED SPUDDED IN COMPLETED PUT TO PRODUCING INITIAL PRODUCTION GRAVITY A.P.I. GOR PRODUCING ZONES TOTAL DEPTH WELL ELEVATION: DATE ABANDONED FIELD: Wildcat 3/86 UNIT COUNTY: Juab Federal #1-9 WELL NO API# 43-023-30013 FT FROM (E) THE LINE LOCATION 1360.5 FT. FROM (N) (\$\text{\$\tex{\$\text{\$\text{\$\text{\$\text{\$\text{\$\text{\$\text{\$\text{\$\text{\$\text{\$\text{\$\}}}}}\$}\text{\$\text{\$\text{\$\text{\$\text{\$\text{\$\text{\$\text{\$\text{\$\}}}}}}}}\endotines}}}}}}}}}}}}}}}}}}}}}}}} 228.5 1/4 - 1/4 SEC. SW NW SE 9

TWP

14\$

RGE.

19W

SEC.

9

OPERATOR

ZEUS ENERGY INC.

SEC.

RGE

TWP

OPERATOR

ZEUS ENERGY INC.

268 South Main Salt Lake City, Utah 84101

531-6764 (secr. for Robert TAYlor) (817

May 18, 1981

Mr. E.W. Guynn, District Engineer U.S. Geological Survey 2000 Administration Bldg. 1745 West 1700 South Salt Lake City, Utah 84104

RE: Zeus Energy, Inc. Federal 1-9 (proposed) Sec. 9, T 14 S, R 19 W Juab County, Utah

Dear Sir:

Enclosed please find Zeus Energy's Application for Permit to Drill the subject well, along with its appropriate plans, as follows:

- 1. Form 9-331C, Application for Permit to Drill, submitted in triplicate.
- Stipulation Rule 30 CFR 221.20, Exception, submitted in triplicate.
- 3./ 10-Point Program complete with exhibits.
- 4. 13-Point Surface Use Plan, complete with exhibits.
- 5. Cultural Resource Survey prepared by the Archaeological Center, University of Utah.

If any additional information is required to expedite the enclosed application, please advise. Your rapid response to this application would be greatly appreciated.

Sincerely,

ZEUS ENERGY, INC.

Robert C. Taylor, President

RDT/dma

cc: State of Utah

Oil & Gas Division Attn: Mike Minder

Form approved. Budget Bureau No. 42-R14

5. LEASE DESIGNATION AND SERIAL NO


U-40560 A


UNITED STATES DEPARTMENT OF THE INTERIOR


GEOLOGICAL SURVEY

UNITED STATES (Other inst. Sons reverse side)

| APPLICATION | V FOR PERMIT | O DRILL, | DEEPI | N, OR PLUG B | ACK | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME |
|--|---|---------------------|--------------------|--|------------|--|
| 1a. TYPE OF WORK | | DEEPE:N | | PLUG BAG | к П | 7. UNIT AGREEMENT NAME |
| b. TYPE OF WELL | | | | 1200 57 (| | |
| OIL C | AS OTHER | | | NGLE X MULTIP | LIC | 8. FARM OR LEASE NAME |
| NAME OF OPERATOR | | | | | | Federal |
| Zeus Ener | rgy, Inc. | | | | | 9. WELL NO. |
| . ADDRESS OF OPERATOR | | | | | | 1-9 |
| 268 South | n Main St., Sali | t Lake City | , Uta | ah, 84101 | | 10. FIELD AND POOL, OR WILDCAT |
| . LOCATION OF WELL (R | eport location clearly and | in accordance wi | th any S | tate requirements.*) | | Wildcat |
| At surface 1360.5 | North and 228. | .b East of | the S | 5年 COK OT | | 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA |
| At proposed prod. zon | 9, T14S, R19W, S | SLB & M | | | | 1 |
| Same a | as above SW⅓. | NW4. SE4 | | | | Sec. 9, T-14-S, R-19-W |
| 4. DISTANCE IN MILES | as above SW2. | REST TOWN OIL POS | T OFFIC | C.* | | 12. COUNTY OR PARISH 13. STATE |
| 45 miles | northwest of De | elta. Utah | | | | Juah Utah |
| 5. DISTANCE FROM PROPO LOCATION TO NEARES | OSED* | | 16. NO |). OF ACRES IN LEASE | | OF ACRES ASSIGNED THIS WELL |
| PROPERTY OR LEASE I | LINE, FT. | 360.5' | 1 12 | 280 | | 40 |
| 8. DISTANCE FROM PROF | OSED LOCATION* | | 1 | OPOSED DEPTH | 20. кот. | ARY OR CABLE TOOLS |
| TO NEAREST WELL, D OR APPLIED FOR, ON TH | RILLING, COMPLETED, | N/A | با ا | 5000' | Ro | tary |
| 1. ELEVATIONS (Show wh | ether DF, RT, GR, etc.) | .,, | <u> </u> | | | 22. APPROX. DATE WORK WILL START* |
| 5400' GR | | | | | | June 20. 1981 |
| 3. | I | PROPOSED CASI | NG ANI | CEMENTING PROGRA | M | · · · · · · · · · · · · · · · · · · · |
| SIZE OF HOLE | SIZE OF CASING | WEIGHT PER F | тоот | SETTING DEPTH | | QUANTITY OF CEMENT |
| 124" | 8 5/8" | 36#/ft | | 500 | Circ | . to surface |
| 7 7/8" | 41/4" | 10.5#/ft | | 5000 | | letermined by logs |
| | | | | DATE: | GAS, | BY THE STATE DIVISION OF AND MINING 20/8/ |
| signed Robert. | drill or deepen directionary. C. Thylor eral or State office use) | ally, give pertinen | pen or pet data of | plug back, give data on pon subsurface locations and president | resent pro | ductive sone and proposed new productive and true vertical depths. Give blowout DATE |
| APPROVED BYCONDITIONS OF APPROV | VAL, IF ANY: | ті | TLE | | | DATE |







** FILE NOTATIONS **

| DATE: July 8, 1981 | |
|--|---|
| | sz. sknc. |
| WELL NO: Federal #1= | 1' |
| Location: Sec. 9 T. | 145 R. 19W County: gual- |
| File Prepared: | Entered on N.I.D: |
| Card Indexed: | Completion Sheet: |
| API | Number <u>43-023-30013</u> |
| CHECKED BY: | |
| Petroleum Engineer: | |
| | |
| | |
| Director: Ok as p | en mle C3 (c) lapo |
| | |
| Administrative Aide: | as Pu Pule C-3, akoranyother |
| oll or gas well. | |
| APPROVAL LETTER: | |
| Bond Required: | Survey Plat Required: |
| Order No. | 0.K. Rule C-3 |
| Rule C-3(c), Topographic within a 660 | Exception - company owns or controls acreage of proposed site |
| Lease Designation Fed | • |
| Appro | oval Letter Written |
| Hot Line P.1 | |

October 20, 1981

Zums Energy, Inc. 268 South Main St., Salt Bake City, Utah 84101

RE: Well No. Federal #1-9, Sec. 9, T. 14S, R. 19W, Juab Countym Utah

Insofar as this office is concerned, approval to drill the above referred to oil well on said unorthodox location is hereby granted in accordance with Rule C-3(c), General Rules and Regulations and Rules of Practice and Procedure.

Should you determine that it will be necessary to plug and abandon this well, you are hereby requested to immediately notify the following:

MICHAEL T. MINDER - Petroleum Engineer

Office: 533-5771 Home: 876-3001

Enclosed please find Form OGC-8-X, which is to be completed whether or not water sands (acquifers) are encountered during drilling. Your cooperation in completing this form will be appreciated.

Further, it is requested that this Division be notified within 24 hours after drilling operations commence, and that the drilling contractor and rig number be identified.

The API number assigned to this well is 43-033-30036.

Sincerely

DIVISION OF OIL, GAS AND MINING

Clean & Jught
Clean B. Feight

Director

CBF/db CC: OGB

October 26, 1981

Zeus Energy, Inc. 268 South Main St. Salt Lake City, Utsh 84101

RE: Well No. Federal #1-9, Sec/ 9, T. 14S, R. 19W, Juab County, Utah

Insofar as this office is concerned, approval to drill the above referred to oil well on said unorthodox location is hereby granted in accordance with Rule C-3(c), General Rules and Regulations and Rules of Practice and Procedure.

Should you determine that it will be necessary to plug and abandon this well, you are hereby requested to immediately notify the following:

MICHAEL T. MINDER - Petroleum Engineer

Office: 533-5771 Home: 876-3001

Enclosed please find Form OGC-8-X, which is to be completed whether or not water sands (acquifers) are encountered during drilling. Your cooperation in completing this form will be appreciated.

Further, it is requested that this Division be notified within 24 hours after drilling operations commence, and that the drilling contractor and rig number be identified.

The API number assigned to this well is 43-023-30013. This is a CORRECTED API number. Please change your records to reflect the new number.

Sincerely

DIVISION OF OIL, GAS AND MINING

Cleon B. Feight Director

CBF/db CC: OGM

ZEUS ENERGY INC.

268 South Main Salt Lake City, Utah 84101

October 14, 1981

Utah State Natural Resources & Energy Department of Oil, Gas & Mining Division 1588 West North Temple Salt Lake City, Utah

Attention: Debbie Beauregard

Re:

Stipulation

Dear Debbie:

As you are aware, Rule 30 CFR 221.20 requires that a well shall not be drilled closer than 200 feet from the lease boundary or 200 feet from any legal subdivision without adequate reasons or consent.

The reason for staking an alternate location is that the preferred location does not fall 200 feet from the south boundary line of the NW 4SE 4 of Section 9, T14S, R19W, SLBM. The reason Drill Hole No. 1 is preferred is because of its practicality, both environmentally and economically. Drill Hole No. 1 is situated at the top of a small drainage system. Drainage control would be minimal with no effect on major drainage systems. This site could be leveled with little cut and fill having to be done. In the event of production, a permanent access road can be built to this location without crossing any drainage systems.

Utah State Natural Resources October 14, 1981 Attn: Debbie Beauregard Page Two

Drill Hole No. 2 satisfies the spacing criteria for staking a drill site, but will require considerably more excavating work than Drill Hole No. 1. Drill Hole No. 2 is situated on the bottom end of a peninsula, between two major drainage systems. Access would require crossing one of these drainage systems. In the event that we wish to deepen the hole in the future and a larger location is needed to accomodate a larger drill rig, Drill Hole No. 1 has plenty of room for expansion without disturbing major drainage systems. Drill Hole No. 2 could be expanded by moving one of the drainage systems laterally or by diverting it at a point above the location.

Therefore, Zeus Energy, Inc., Lessee, requests your consent to the drilling of the proposed well at the above-described location. In consideration of such consent, Zeus Energy, Inc., Lessee, hereby expressly covenants and agrees that it will make no separate assignments of the NW\\$SE\\$ and the SW\\$SE\\$ of Section 9, T14S, R19W, SLBM, and that it will keep the two described subdivisions under joint assignment until the above-mentioned well has been plugged and abandoned with the approval of the Supervisor.


Please find enclosed a complete drawing of Section 9, per your request. The drawing together with a copy of the lease payment should satisfy your requirement for evidence of property ownership withtin 660 feet of the drill site.


Very truly yours,

ZEUS ENERGY, INC.


Robert C. Taxlor, President


RCT:prb Enclosures





NOTICE OF PAYMENT DUE **RETURN THIS NOTICE WITH REMITTANCE TO:** 40560 **BUREAU OF LAND MANAGEMENT** ADP- 4613 TEMPLE, SALT LAKE CTY MAKE REMITTANCE PAYABLE TO: RECEIVED THE BUREAU OF LAND MANAGEMENT This is a courteey billing notice for a rental 150 030 24 PM 1: 08 (PFX=U) OGP 49 023 14 DEPT OF INTERIOR BUR. OF LAND MGMT. ZEUS ENERGY INC 268 S MAIN 84101 DO NOT WRITE IN THIS BLOCK IF THE ABOVE ADDRESS IS INCORRECT, PLEASE ENTER CORRECT





Rule 30 CFR 221.20 requires well shall not be drilled closer than 200 ft. from the lease boundary or 200 ft. from any legal subdivision without adequate reasons or consent.

District Oil and Gas Engineer U.S. Geological Survey Conservation Division 8440 Federal Building Slat Lake City, Utah 84138

Re: Stipulation

Dear Sir:

Zeus Energy, Inc., is the owner of U.S. Oil and Gas Lease U-40560, and proposes to drill a well on the leased premises to test for oil and gas at a location in the SW4, NW4 SE4 Section 9, T 14 S, R 19 W, S.L.B. Mer., Juab County, State of Utah, 1360.5' North and 228.5 ' east of the S4 corner of Section 9.

Section 221.20 of the Federal Oil and Gas Regulations requires that no well be drilled less than 200' from the boundary of any legal subdivision without the written consent of the Supervisor, United States Geological Survey. The proposed location is approximately 40' from the South boundary line of the NW_4 SE $_4$ of Section 9, but is considered to be necessary because of the following:

The reason for staking an alternate location is that the preferred location does not fall 200 feet from the south boundary line of the northwest 1/4 of the southeast 1/4 of Section 9, Township 14 South, Range 19 West, Salt Lake Base and Meridian. The reason Drill Hole No. 1 is preferred is because of its practicality, both environmentally and economically. Drill Hole No. 1 is situated at the top of a small drainage system. Drainage control would be minimal with no effect on major drainage systems. This site could be leveled with little cut and fill having to be done. In the event of production a permanent access road can be built to this location without crossing any drainage systems. Drill Hole No. 2 satisfies the spacing criteria for staking a drill site, but will require considerably more excavating work than Drill Hole No. 1. Drill Hole No. 2 is situated on the bottom end of a peninsula, between two major drainage systems. Access would require crossing one of these drainage systems. In the event that we wish to deepen the hole in the future and a larger location is needed to accomodate a larger drill rig, Drill Hole No. 1 has plenty of room for expansion without disturbing major drainage systems. Drill Hole No. 2 could be expanded by moving one of the drainage systems laterally or by diverting it at a point above the location.

Therefore, Zeus Energy, Inc., Lessee, requests the consent of the Supervisor to the drilling of the proposed well at the above-described location. In consideration of such consent, Zeus Energy, Inc., Lessee, heregy expressly covenants and agrees that he will make no separate assignments of the NW4 SE4 and the SW4 SE4, Section 9, T 14 S, R 19 W, SLB Mer., and that he will keep the two described subdivisions under joint assignment until the abovementioned well has been plugged and abandoned with the approval of the Supervisor.

Very truly yours,

ZEUS ENERGY, INC.

Robert Taylor, President


10 POINT PLAN

ZEUS ENERGY, INC. Section 9, T14S, R19W Juab County, Utah

| Unknown; no geological markers: Unknown; no geological well control in the area. Estimated depths anticipated to encounter water, oil, gas or other mineral ing formations: Unknown; see Item #2, above. Casing program: See Form OGC-la, Item #23 | |
|---|-------------|
| Estimated depths anticipated to encounter water, oil, gas or other mineral ing formations: Unknown; see Item #2, above. Casing program: | |
| ing formations: Unknown; see Item #2, above. Casing program: | |
| ing formations: Unknown; see Item #2, above. Casing program: | |
| ing formations: Unknown; see Item #2, above. Casing program: | |
| ing formations: Unknown; see Item #2, above. Casing program: | |
| ing formations: Unknown; see Item #2, above. | |
| ing formations: Unknown; see Item #2, above. Casing program: | |
| ing formations: Unknown; see Item #2, above. Casing program: | neral b |
| Casing program: | |
| | |
| | |
| See Form OGC-1a, Item #23 | |
| | |
| | |
| | |

| Dlawayt Drawante | unga Hudunulda daw | bla wama with a | 2000 noi mating | POD One co |
|------------------|---------------------------|------------------|-------------------|------------|
| | ors: <u>Hydraulic dou</u> | | | |
| | 11 be provided for | | | |
| | will be installed | | | |
| | ine will be 2", 30 | | BOP will be teste | |
| | Daily Drilling Rep | | | |
| | t, BOP will be tes | | | hereafter, |
| the BOP will b | e checked daily fo | r mechanical ope | erations only and | will be |
| noted on the I | ADC Report. See E | xhibit 'A'. | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | *** | | |
| Mud Program: | | | , | |
| Approximate | | Weight | | |
| Interval | Type Mud | #ergnc ≓/gal. | Viscosity | W.L. |
| 0 - 500' | Native | 8.3 - 8.5 | As needed | NC |
| 500 - 5000' | Gel/low solids | 8.5 - 9.0 | 32 - 35 | 10 - 15 c |
| 300 0000 | 4017 1011 301140 | | | |
| | | | | |
| | **** | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| Auxillary Equipo | ment: | | <u> </u> | |
| a. Kelly cock | will be in use at | all times. | | |
| b. Full openi | ng stabbing valve | will be present | on floor at all | times. |
| c. Mud monito | oring will be visua | 1. No abnormal | pressures are an | ticipated. |
| | si choke manifold | | | |
| See Exhibi | | | | |
| | | | | |
| | | | | |
| | | | | ····· |

| _ | |
|------|--|
| 8. | Testing Program: |
| | No DST's planned. No cores anticipated. Open hole logs will be DIL and |
| | Neutron-Density log with caliper. If casing is run, a cement bond log |
| | with Gamma Ray will be run. |
| | |
| | |
| 9. | Hazards: |
| ٠. | No abnormal pressures, temperatures, or poison gases are expected to be |
| | encountered. |
| .3 | encountered. |
| | |
| 10. | The starting date is approximately |
| 10. | on rig availability and should take 2 to 3 weeks to complete. |
| | on rig availability and should take to complete. |
| | |
| I he | ereby certify that I, or persons under my direct supervision, have inspected the |
| pro | posed drill site and access route; that I am familiar with the conditions which |
| pre: | sently exist; that the statements made in this plan are, to the best of my know- ge, true and correct; and, that the work associated with the operations proposed |
| here | ein will be performed by <u>Zeus Energy</u> , Inc., its contractors and subcontractors in conformity with this plan and the terms |
| and | its contractors and subcontractors in conformity with this plan and the terms conditions under which it is approved. |
| anu | Conditions under which it is approved. |
| | |
| | h . 16 1601 |
| | May 18, 1981 |
| | U Date |
| | Date Name Name |
| | Name _ / / |



All equipment to be 3,000 psi working pressure except as noted.

Rd Double ram type preventer with two sets of rams.

R ... Single ram type preventer with one set of rams.

S Drilling spool with side outlet connections for chake and kill lines.

A Annular type blowout preventer.

Exhibit 'A'

Zeus Energy, Inc. Federal 1-9 (proposed) Section 9 T 14 S, R 19 W Juab County, Utah

Required Minimum Blowout Preventer and Choke Manifold

13 POINT SURFACE USE PLAN

Zeus Energy, Inc.
Federal 1-9 (Proposed)
Sec. 9, T 14 S, R19 W
Juab County, Utah

| Exi | sting Roads |
|-------------|--|
| <u>a.</u> | Proposed Wellsite Location: |
| | As surveyed by a registered land surveyor is located 1360.5' north and 228.5' |
| | of S ¹ ₄ corner, Section 9, T 14 S, R 19 W, Juab County, Utah. See |
| | Exhibit I. |
| | |
| b. | Planned Access Route: |
| | From Gandy, Utah, drive northeast 10.7 miles on a light duty dirt road. |
| | Turn west (left) onto another light duty dirt road which is the main |
| | access road to Pleasant Vally. Go west approximately 5 miles. The |
| | location will be approximately 250' from the road. |
| | See Exhibit II |
| | |
| | |
| | |
| | |
| | |
| <u>c.</u> | Access Road Labeled: |
| | See Exhibit II. Red - existing road |
| | Blue - New access road to be constructed |
| | |
| | |
| | |
| <u>d.</u> | If exploratory well, all existing roads within 3 miles: |
| | See Exhibit II. |
| | See LAMSTO II. |
| | See Lambic II. |

| f. Plans for improvement and/or maintenance of existing roads: The existing roads will require minor improvements. However, these roads, along with the new access road, may require periodic grading to return the road surface to a corss section necassary for proper drainage. Planned Access Route Route Location: The planned new access route was selected to provide the shortest distance to the wellsite with acceptable grades from the main connector road. The new access road will be approximately 250' from the existing improved dirt road. A temporary access will be built initially: if the well is productive, the temporary road will be improved as follows: (1) Width: The average dirt width will be 20 feet. The average traveled surface width will be 20 feet. Road construction will be in accordance with typical roadways requested by the US Bureau of Land Management. (2) Maximum Grades: The maximum grade allowed will be 5°. (3) Turnouts: Not required. (4) Drainage Design: Prior to construction of the new access road, the brush and topsoil will be sindrowed to each side of the alignme outside construction limits. The subgrade surface will be a minimum elevation of one foot above ditch grade. The road surface will be center crowned and the inslopes will have a maximum slope of 3:1 and fill slopes will be a maximum of 2:1. | e. | If development well, all existing roads within a one mile radius of well- |
|---|----------|---|
| f. Plans for improvement and/or maintenance of existing roads: The existing roads will require minor improvements. However, these roads, along with the new access road, may require periodic grading to return the road surface to a corss section necassary for proper drainage. Planned Access Route Route Location: The planned new access route was selected to provide the shortest distance to the wellsite with acceptable grades from the main connector road. The new access road will be approximately 250' from the existing improved dirt road. A temporary access will be built initially: if the well is productive, the temporary road will be improved as follows: (1) Width: The average dirt width will be 20 feet. The average traveled surface width will be 20 feet. Road construction will be in accordance with typical roadways requested by the US Bureau of Land Management. (2) Maximum Grades: The maximum grade allowed will be 5°. (3) Turnouts: Not required. (4) Drainage Design: Prior to construction of the new access road, the brush and topsoil will be sindrowed to each side of the alignme outside construction limits. The subgrade surface will be a minimum elevation of one foot above ditch grade. The road surface will be center crowned and the inslopes will have a | | site: |
| The existing roads will require minor improvements. However, these roads, along with the new access road, may require periodic grading to return the road surface to a corss section necassary for proper drainage. Planned Access Route Route Location: The planned new access route was selected to provide the shortest distance to the wellsite with acceptable grades from the main connector road. The new access road will be approximately 250' from the existing improved dirt road. A temporary access will be built initially: if the well is productive, the temporary road will be improved as follows: (1) Width: The average dirt width will be 20 feet. The average traveled surface width will be 20 feet. Road construction will be in accordance with typical roadways requested by the US Bureau of Land Management. (2) Maximum Grades: The maximum grade allowed will be 5°. (3) Turnouts: Not required. (4) Drainage Design: Prior to construction of the new access road, the brush and topsoil will be sindrowed to each side of the alignme outside construction limits. The subgrade surface will be a minimum elevation of one foot above ditch grade. The road surface will be center crowned and the inslopes will have a | | N/A |
| The existing roads will require minor improvements. However, these roads, along with the new access road, may require periodic grading to return the road surface to a corss section necassary for proper drainage. Planned Access Route Route Location: The planned new access route was selected to provide the shortest distance to the wellsite with acceptable grades from the main connector road. The new access road will be approximately 250' from the existing improved dirt road, A temporary access will be built initially: if the well is productive, the temporary road will be improved as follows: (1) Width: The average dirt width will be 20 feet. The average traveled surface width will be 20 feet. Road construction will be in accordance with typical roadways requested by the US Bureau of Land Management. (2) Maximum Grades: The maximum grade allowed will be 5°. (3) Turnouts: Not required. (4) Drainage Design: Prior to construction of the new access road, the brush and topsoil will be sindrowed to each side of the alignme outside construction limits. The subgrade surface will be a minimum elevation of one foot above ditch grade. The road surface will be center crowned and the inslopes will have a | | |
| The existing roads will require minor improvements. However, these roads, along with the new access road, may require periodic grading to return the road surface to a corss section necassary for proper drainage. Planned Access Route Route Location: The planned new access route was selected to provide the shortest distance to the wellsite with acceptable grades from the main connector road. The new access road will be approximately 250' from the existing improved dirt road. A temporary access will be built initially: if the well is productive, the temporary road will be improved as follows: (1) Width: The average dirt width will be 20 feet. The average traveled surface width will be 20 feet. Road construction will be in accordance with typical roadways requested by the US Bureau of Land Management. (2) Maximum Grades: The maximum grade allowed will be 5°. (3) Turnouts: Not required. (4) Drainage Design: Prior to construction of the new access road, the brush and topsoil will be sindrowed to each side of the alignme outside construction limits. The subgrade surface will be a minimum elevation of one foot above ditch grade. The road surface will be center crowned and the inslopes will have a | | |
| The existing roads will require minor improvements. However, these roads, along with the new access road, may require periodic grading to return the road surface to a corss section necassary for proper drainage. Planned Access Route Route Location: The planned new access route was selected to provide the shortest distance to the wellsite with acceptable grades from the main connector road. The new access road will be approximately 250' from the existing improved dirt road. A temporary access will be built initially: if the well is productive, the temporary road will be improved as follows: (1) Width: The average dirt width will be 20 feet. The average traveled surface width will be 20 feet. Road construction will be in accordance with typical roadways requested by the US Bureau of Land Management. (2) Maximum Grades: The maximum grade allowed will be 5°. (3) Turnouts: Not required. (4) Drainage Design: Prior to construction of the new access road, the brush and topsoil will be sindrowed to each side of the alignme outside construction limits. The subgrade surface will be a minimum elevation of one foot above ditch grade. The road surface will be center crowned and the inslopes will have a | | |
| The existing roads will require minor improvements. However, these roads, along with the new access road, may require periodic grading to return the road surface to a corss section necassary for proper drainage. Planned Access Route Route Location: The planned new access route was selected to provide the shortest distance to the wellsite with acceptable grades from the main connector road. The new access road will be approximately 250' from the existing improved dirt road. A temporary access will be built initially: if the well is productive, the temporary road will be improved as follows: (1) Width: The average dirt width will be 20 feet. The average traveled surface width will be 20 feet. Road construction will be in accordance with typical roadways requested by the US Bureau of Land Management. (2) Maximum Grades: The maximum grade allowed will be 5°. (3) Turnouts: Not required. (4) Drainage Design: Prior to construction of the new access road, the brush and topsoil will be sindrowed to each side of the alignme outside construction limits. The subgrade surface will be a minimum elevation of one foot above ditch grade. The road surface will be center crowned and the inslopes will have a | | |
| The existing roads will require minor improvements. However, these roads, along with the new access road, may require periodic grading to return the road surface to a corss section necassary for proper drainage. Planned Access Route Route Location: The planned new access route was selected to provide the shortest distance to the wellsite with acceptable grades from the main connector road. The new access road will be approximately 250' from the existing improved dirt road. A temporary access will be built initially: if the well is productive, the temporary road will be improved as follows: (1) Width: The average dirt width will be 20 feet. The average traveled surface width will be 20 feet. Road construction will be in accordance with typical roadways requested by the US Bureau of Land Management. (2) Maximum Grades: The maximum grade allowed will be 5°. (3) Turnouts: Not required. (4) Drainage Design: Prior to construction of the new access road, the brush and topsoil will be sindrowed to each side of the alignme outside construction limits. The subgrade surface will be a minimum elevation of one foot above ditch grade. The road surface will be center crowned and the inslopes will have a | f. | Plans for improvement and/or maintenance of existing roads: |
| to return the road surface to a corss section necassary for proper drainage. Planned Access Route Route Location: The planned new access route was selected to provide the shortest distance to the wellsite with acceptable grades from the main connector road. The new access road will be approximately 250' from the existing improved dirt road. A temporary access will be built initially: if the well is productive, the temporary road will be improved as follows: (1) Width: The average dirt width will be 20 feet. The average traveled surface width will be 20 feet. Road construction will be in accordance with typical roadways requested by the US Bureau of Land Management. (2) Maximum Grades: The maximum grade allowed will be 5°. (3) Turnouts: Not required. (4) Drainage Design: Prior to construction of the new access road, the brush and topsoil will be sindrowed to each side of the alignme outside construction limits. The subgrade surface will be a minimum elevation of one foot above ditch grade. The road surface will be center crowned and the inslopes will have a | <u> </u> | |
| Planned Access Route Route Location: The planned new access route was selected to provide the shortest distance to the wellsite with acceptable grades from the main connector road. The new access road will be approximately 250' from the existing improved dirt road. A temporary access will be built initially: if the well is productive, the temporary road will be improved as follows: (1) Width: The average dirt width will be 20 feet. The average traveled surface width will be 20 feet. Road construction will be in accordance with typical roadways requested by the US Bureau of Land Management. (2) Maximum Grades: The maximum grade allowed will be 5°. (3) Turnouts: Not required. (4) Drainage Design: Prior to construction of the new access road, the brush and topsoil will be sindrowed to each side of the alignme outside construction limits. The subgrade surface will be a minimum elevation of one foot above ditch grade. The road surface will be center crowned and the inslopes will have a | | these roads, along with the new access road, may require periodic grading |
| Planned Access Route Route Location: The planned new access route was selected to provide the shortest distance to the wellsite with acceptable grades from the main connector road. The new access road will be approximately 250' from the existing improved dirt road. A temporary access will be built initially: if the well is productive, the temporary road will be improved as follows: (1) Width: The average dirt width will be 20 feet. The average traveled surface width will be 20 feet. Road construction will be in accordance with typical roadways requested by the US Bureau of Land Management. (2) Maximum Grades: The maximum grade allowed will be 50. (3) Turnouts: Not required. (4) Drainage Design: Prior to construction of the new access road, the brush and topsoil will be sindrowed to each side of the alignme outside construction limits. The subgrade surface will be a minimum elevation of one foot above ditch grade. The road surface will be center crowned and the inslopes will have a | | to return the road surface to a corss section necassary for proper |
| Route Location: The planned new access route was selected to provide the shortest distance to the wellsite with acceptable grades from the main connector road. The new access road will be approximately 250' from the existing improved dirt road. A temporary access will be built initially; if the well is productive, the temporary road will be improved as follows: (1) Width: The average dirt width will be 20 feet. The average traveled surface width will be 20 feet. Road construction will be in accordance with typical roadways requested by the US Bureau of Land Management. (2) Maximum Grades: The maximum grade allowed will be 5°. (3) Turnouts: Not required. (4) Drainage Design: Prior to construction of the new access road, the brush and topsoil will be sindrowed to each side of the alignme outside construction limits. The subgrade surface will be a minimum elevation of one foot above ditch grade. The road surface will be center crowned and the inslopes will have a | | drainage. |
| Route Location: The planned new access route was selected to provide the shortest distance to the wellsite with acceptable grades from the main connector road. The new access road will be approximately 250' from the existing improved dirt road. A temporary access will be built initially; if the well is productive, the temporary road will be improved as follows: (1) Width: The average dirt width will be 20 feet. The average traveled surface width will be 20 feet. Road construction will be in accordance with typical roadways requested by the US Bureau of Land Management. (2) Maximum Grades: The maximum grade allowed will be 5°. (3) Turnouts: Not required. (4) Drainage Design: Prior to construction of the new access road, the brush and topsoil will be sindrowed to each side of the alignme outside construction limits. The subgrade surface will be a minimum elevation of one foot above ditch grade. The road surface will be center crowned and the inslopes will have a | | |
| Noute Location: The planned new access route was selected to provide the shortest distance to the wellsite with acceptable grades from the main connector road. The new access road will be approximately 250' from the existing improved dirt road. A temporary access will be built initially; if the well is productive, the temporary road will be improved as follows: (1) Width: The average dirt width will be 20 feet. The average traveled surface width will be 20 feet. Road construction will be in accordance with typical roadways requested by the US Bureau of Land Management. (2) Maximum Grades: The maximum grade allowed will be 5°. (3) Turnouts: Not required. (4) Drainage Design: Prior to construction of the new access road, the brush and topsoil will be sindrowed to each side of the alignme outside construction limits. The subgrade surface will be a minimum elevation of one foot above ditch grade. The road surface will be center crowned and the inslopes will have a | | |
| Route Location: The planned new access route was selected to provide the shortest distance to the wellsite with acceptable grades from the main connector road. The new access road will be approximately 250' from the existing improved dirt road. A temporary access will be built initially; if the well is productive, the temporary road will be improved as follows: (1) Width: The average dirt width will be 20 feet. The average traveled surface width will be 20 feet. Road construction will be in accordance with typical roadways requested by the US Bureau of Land Management. (2) Maximum Grades: The maximum grade allowed will be 5°. (3) Turnouts: Not required. (4) Drainage Design: Prior to construction of the new access road, the brush and topsoil will be sindrowed to each side of the alignme outside construction limits. The subgrade surface will be a minimum elevation of one foot above ditch grade. The road surface will be center crowned and the inslopes will have a | | |
| Route Location: The planned new access route was selected to provide the shortest distance to the wellsite with acceptable grades from the main connector road. The new access road will be approximately 250' from the existing improved dirt road. A temporary access will be built initially; if the well is productive, the temporary road will be improved as follows: (1) Width: The average dirt width will be 20 feet. The average traveled surface width will be 20 feet. Road construction will be in accordance with typical roadways requested by the US Bureau of Land Management. (2) Maximum Grades: The maximum grade allowed will be 5°. (3) Turnouts: Not required. (4) Drainage Design: Prior to construction of the new access road, the brush and topsoil will be sindrowed to each side of the alignme outside construction limits. The subgrade surface will be a minimum elevation of one foot above ditch grade. The road surface will be center crowned and the inslopes will have a | 01 a | nnad Access Poute |
| shortest distance to the wellsite with acceptable grades from the main connector road. The new access road will be approximately 250' from the existing improved dirt road. A temporary access will be built initially; if the well is productive, the temporary road will be improved as follows: (1) Width: The average dirt width will be 20 feet. The average traveled surface width will be 20 feet. Road construction will be in accordance with typical roadways requested by the US Bureau of Land Management. (2) Maximum Grades: The maximum grade allowed will be 5°. (3) Turnouts: Not required. (4) Drainage Design: Prior to construction of the new access road, the brush and topsoil will be sindrowed to each side of the alignme outside construction limits. The subgrade surface will be a minimum elevation of one foot above ditch grade. The road surface will be center crowned and the inslopes will have a | | |
| connector road. The new access road will be approximately 250' from the existing improved dirt road. A temporary access will be built initially: if the well is productive, the temporary road will be improved as follows: (1) Width: The average dirt width will be 20 feet. The average traveled surface width will be 20 feet. Road construction will be in accordance with typical roadways requested by the US Bureau of Land Management. (2) Maximum Grades: The maximum grade allowed will be 5°. (3) Turnouts: Not required. (4) Drainage Design: Prior to construction of the new access road, the brush and topsoil will be sindrowed to each side of the alignme outside construction limits. The subgrade surface will be a minimum elevation of one foot above ditch grade. The road surface will be center crowned and the inslopes will have a | | |
| existing improved dirt road. A temporary access will be built initially: if the well is productive, the temporary road will be improved as follows: (1) Width: The average dirt width will be 20 feet. The average traveled | | |
| the well is productive, the temporary road will be improved as follows: (1) Width: The average dirt width will be 20 feet. The average traveled surface width will be 20 feet. Road construction will be in accordance with typical roadways requested by the US Bureau of Land Management. (2) Maximum Grades: The maximum grade allowed will be 5°. (3) Turnouts: Not required. (4) Drainage Design: Prior to construction of the new access road, the brush and topsoil will be sindrowed to each side of the alignme outside construction limits. The subgrade surface will be a minimum elevation of one foot above ditch grade. The road surface will be center crowned and the inslopes will have a | | |
| (1) Width: The average dirt width will be 20 feet. The average traveled surface width will be 20 feet. Road construction will be in accordance with typical roadways requested by the US Bureau of Land Management. (2) Maximum Grades: The maximum grade allowed will be 5°. (3) Turnouts: Not required. (4) Drainage Design: Prior to construction of the new access road, the brush and topsoil will be sindrowed to each side of the alignme outside construction limits. The subgrade surface will be a minimum elevation of one foot above ditch grade. The road surface will be center crowned and the inslopes will have a | | |
| surface width will be 20 feet. Road construction will be in accordance with typical roadways requested by the US Bureau of Land Management. (2) Maximum Grades: The maximum grade allowed will be 5°. (3) Turnouts: Not required. (4) Drainage Design: Prior to construction of the new access road, the brush and topsoil will be sindrowed to each side of the alignme outside construction limits. The subgrade surface will be a minimum elevation of one foot above ditch grade. The road surface will be center crowned and the inslopes will have a | | |
| accordance with typical roadways requested by the US Bureau of Land Management. (2) Maximum Grades: The maximum grade allowed will be 5°. (3) Turnouts: Not required. (4) Drainage Design: Prior to construction of the new access road, the brush and topsoil will be sindrowed to each side of the alignme outside construction limits. The subgrade surface will be a minimum elevation of one foot above ditch grade. The road surface will be center crowned and the inslopes will have a | | |
| Land Management. (2) Maximum Grades: The maximum grade allowed will be 5°. (3) Turnouts: Not required. (4) Drainage Design: Prior to construction of the new access road, the brush and topsoil will be sindrowed to each side of the alignme outside construction limits. The subgrade surface will be a minimum elevation of one foot above ditch grade. The road surface will be center crowned and the inslopes will have a | | |
| (2) Maximum Grades: The maximum grade allowed will be 5⁰. (3) Turnouts: Not required. (4) Drainage Design: Prior to construction of the new access road, the brush and topsoil will be sindrowed to each side of the alignme outside construction limits. The subgrade surface will be a minimum elevation of one foot above ditch grade. The road surface will be center crowned and the inslopes will have a | | |
| (3) Turnouts: Not required. (4) Drainage Design: Prior to construction of the new access road, the brush and topsoil will be sindrowed to each side of the alignme outside construction limits. The subgrade surface will be a minimum elevation of one foot above ditch grade. The road surface will be center crowned and the inslopes will have a | | |
| (4) Drainage Design: Prior to construction of the new access road, the brush and topsoil will be sindrowed to each side of the alignme outside construction limits. The subgrade surface will be a minimum elevation of one foot above ditch grade. The road surface will be center crowned and the inslopes will have a | | |
| brush and topsoil will be sindrowed to each side of the alignme outside construction limits. The subgrade surface will be a minimum elevation of one foot above ditch grade. The road surface will be center crowned and the inslopes will have a | | |
| outside construction limits. The subgrade surface will be a minimum elevation of one foot above ditch grade. The road surface will be center crowned and the inslopes will have a | (4 | |
| minimum elevation of one foot above ditch grade. The road surface will be center crowned and the inslopes will have a | | |
| surface will be center crowned and the inslopes will have a | | |
| | | |
| maximum stope of 3:1 and fill stopes will be a maximum of 2:1. | | |
| | | maximum stope of 3:1 and fill stopes will be a maximum of 2:1. |
| | | |

- (5) Culverts Use, Major Cuts and Fills: Culverts will not be required.

 Cuts and fills will be minimal.
- (6) Surfacing Material: The proposed access road will be constructed with native fill.
- (7) Gates, Cattlegurads, Fence Cuts: Not required.
- (8) New Portion of road will be center flagged.

| abar | doned, temporarily abandoned, disposal and drilling) within a 2 mile |
|-------------------|--|
| radi | us. |
| | |
| | |
| | |
| | |
| .ocat | ion of Existing and/or Proposed Facilities |
| ı. Ex | isting facilities within one mile radius owned or controlled by opera |
| (1) | Tank Batteries: None |
| (2) | Production Facilities: None |
| (3) | Oil Gathering Lines: Nore |
| (4) | Gas Gathering Lines: None |
| (5) | Injection Lines: None |
| (6) | Disposal Lines: None |
| | |
| | |
| | |
| | |
| N | ew Facilities in Event of Production: |
| | ew Facilities in Event of Production: New facilities: wellhead, condensate tank, production separator, |
| o. N | New facilities: wellhead, condensate tank, production separator, |
| (1) | |
| (1) | New facilities: wellhead, condensate tank, production separator, meter house, all constructed on disturbed ground. Dimension of the facilities are shown on Exhibit III. |
| (1) | New facilities: wellhead, condensate tank, production separator, meter house, all constructed on disturbed ground. Dimension of the facilities are shown on Exhibit III. Construction will be to strip the topsoil and level the drilling pad |
| (1) | New facilities: wellhead, condensate tank, production separator, meter house, all constructed on disturbed ground. Dimension of the facilities are shown on Exhibit III. Construction will be to strip the topsoil and level the drilling pad. Construction methods will be employed to assure that no drainage flow |
| (1) | New facilities: wellhead, condensate tank, production separator, meter house, all constructed on disturbed ground. Dimension of the facilities are shown on Exhibit III. Construction will be to strip the topsoil and level the drilling pad. Construction methods will be employed to assure that no drainage flow are impounded to prevent the loss of any hydrocarbons from the site in |
| (1) (2) (3) | New facilities: wellhead, condensate tank, production separator, meter house, all constructed on disturbed ground. Dimension of the facilities are shown on Exhibit III. Construction will be to strip the topsoil and level the drilling pad. Construction methods will be employed to assure that no drainage flow are impounded to prevent the loss of any hydrocarbons from the site facilitate rapid clean up and recovery of the loss. |
| (1) | New facilities: wellhead, condensate tank, production separator, meter house, all constructed on disturbed ground. Dimension of the facilities are shown on Exhibit III. Construction will be to strip the topsoil and level the drilling pad. Construction methods will be employed to assure that no drainage flow are impounded to prevent the loss of any hydrocarbons from the site facilitate rapid clean up and recovery of the loss. Protective measures to protect wildlife and livestock: Open pits will |
| (1) (2) (3) | New facilities: wellhead, condensate tank, production separator, meter house, all constructed on disturbed ground. Dimension of the facilities are shown on Exhibit III. Construction will be to strip the topsoil and level the drilling pad. Construction methods will be employed to assure that no drainage flow are impounded to prevent the loss of any hydrocarbons from the site facilitate rapid clean up and recovery of the loss. |
| (1) (2) (3) | New facilities: wellhead, condensate tank, production separator, meter house, all constructed on disturbed ground. Dimension of the facilities are shown on Exhibit III. Construction will be to strip the topsoil and level the drilling pad. Construction methods will be employed to assure that no drainage flow are impounded to prevent the loss of any hydrocarbons from the site facilitate rapid clean up and recovery of the loss. Protective measures to protect wildlife and livestock: Open pits will |
| (1) (2) (3) | New facilities: wellhead, condensate tank, production separator, meter house, all constructed on disturbed ground. Dimension of the facilities are shown on Exhibit III. Construction will be to strip the topsoil and level the drilling pad. Construction methods will be employed to assure that no drainage flow are impounded to prevent the loss of any hydrocarbons from the site facilitate rapid clean up and recovery of the loss. Protective measures to protect wildlife and livestock: Open pits will |
| (1) (2) (3) | New facilities: wellhead, condensate tank, production separator, meter house, all constructed on disturbed ground. Dimension of the facilities are shown on Exhibit III. Construction will be to strip the topsoil and level the drilling pad. Construction methods will be employed to assure that no drainage flow are impounded to prevent the loss of any hydrocarbons from the site facilitate rapid clean up and recovery of the loss. Protective measures to protect wildlife and livestock: Open pits will |

| | Plan for rehabilitation of disturbed areas no longer needed for operations er construction is completed: |
|-----------|---|
| | |
| • | on completion of well, areas required for continued use will be graded to |
| | rovide drainage and minimize erosion. Those areas not required for con- |
| | nued use will be graded to blend with the surrounding topography. Topsoil libe replaced on those areas and seeded as per BLM specification. |
| | |
| | |
| | |
| | |
| | |
| Loc | ation and Type of Water Supply |
| <u>a.</u> | The water source has not yet been determined but will be from a legal |
| | private source. |
| b. | Water transportation system: water will be hauled in trucks from an |
| | undetermined source. |
| c. | Water wells: None |
| | |
| | |
| | |
| | |
| | C. Constitution Makeuiale |
| Sou | rce of Construction Materials |
| <u>a.</u> | |
| | the boundaries of the proposed site. Topsoil will be stripped |
| | to a depth of 6 inches and stockpiles in an area that does not |
| | interfere with operations. |
| <u>b.</u> | |
| | ministered by the U.S. Department of the Interior, U.S. Bureau |
| | of Land Management. |
| <u>c.</u> | Materials Foreigh to Site: N/A |
| d. | Access road shown under Item II. |
| | |
| | |

| <u>a.</u> | Cuttings: | Will be contained within the limits of the reserve pit. |
|-------------|---------------------------------------|---|
| b. | Drilling | Fluids: Will be retained in the reserve pit. |
| | | |
| <u> </u> | Produced | Fluids: No substantial amount of water is expected. The amount |
| | | of hydrocarbon that may be produced while treating will be re- |
| | | tained in the reserve pit. Previous to clean up operations the |
| | | hydrocarbon materials will be skimmed or removed as the situation |
| | | would dictate. |
| | · · · · · · · · · · · · · · · · · · · | |
| | Sewage: | Sanitary facilities will consist of at least one chemical toilet |
| <u> </u> | 00,1430 | Waste will be contained in a pit and backfilled immediately |
| | | following the drilling operations or removed to a sanitary |
| | | disposal facility. |
| | | |
| —— е. | Garbage: | A burn cage will be constructed and fenced with small mesh wire. |
| <u></u> | dar bage. | The refuse will be removed from the area and taken to a landfill |
| | | |
| | Clean Up | Well Site: After drilling, the surface of the drill pad will be |
| | <u> </u> | cleaned and graded to accomodate a completion rig. The "mouse |
| | | hole and rat hole" will be backfilled to prevent injury and |
| | | hazard for livestock. Reserve pit will be fneced until dry and |
| | | it can be backfilled and restored to natural terrain. |
| | | |
| | | |
| | | |
| | ••• | 27242 |
| | illary Fac | |
| <u>Nor</u> | <u>ne required</u> | |
| | | |
| | · · · · · · · · · · · · · · · · · · · | - |
| | | |
| | | |
| - | | |
| | | • |

| 9. Well-s | ite Layout |
|-----------|------------|
|-----------|------------|

| (1) | Well location is relatively flat and requires minimal cuts and fills. |
|-----|---|
| | Any cuts and fills needed will be determined at on-site inspection. |
| | Surface soil will be stock piled on the north side of location, 12" high. |
| (2) | Location of Pits: See Exhibit IV. |
| (3) | Rig orientation: See Exhibit IV. |
| (4) | Pits will be unlined, unless otherwise required. |
| | |
| | |
| | |
| | |
| | |
| | |

10. Plans For Restoration of Surface

- a. Reserve Pit Cleanup: The pit will be fenced prior to rig release and shall be maintained until clean up. Previous to backfill operation, any hydrocarbon material on the pit surface will be removed. The fluids and solids contained in the pit shall be backfilled with soil excavated from the site and with soil adjacent to the reserve pit. The restored surface of the reserve pit will be contoured to prevent impoundment of any drainage flows. The gradient of the surface will be maintained to prevent sudden acceleration of drainage flows which could cause continued erosion of the surface. Following backfill completion, topsoil removed from the disturbed areas will be replaced in a uniform layer. The reserve pit will be seeded per BLM recommendation during the appropriate season following final restoration of the site.
- b. Restoration Plans Production Developed: The reserve pit will be back-filled and restored as described under Item a. In addition, those disturbed areas not required for production will be graded to blend with the surrounding topography. Topsoil will be placed on these areas and seeded. The portion of the drill pad required for production and turning areas will be graded to minimize erosion and provide access to production facilities under inclument conditions. Following final improvement and surfacing of that portion of new access road, the topsoil windrowed to each side of the alignment will be placed on the cut slopes. Following depleticn and abandonment of the site, restoration procedures will be those that follow under Item c.

| C. K62 | toration Plans - No Production Developed: Of course, the reserve pit |
|---|--|
| will be | restored as described above. With no production developed, the enti |
| surface | disturbed by construction of the drilling pad will be restored to it |
| natural | terrain and reseeded per BLM requirements |
| | |
| *************************************** | |
| | |
| Other I | nformation |
| | face Description: The proposed site is located in Pleasant Valley |
| | ich drains into Snake Valley from the southern end of the Deep Creek |
| | ns. The site is siutated on two low swells at the toe of a broad |
| | 1 fan. The vegetation is sparse, consisting of annuals and grasses i |
| | sed with occassional salt brush on the low swells with sagebrush, rab |
| | |
| brush a | nd snakeweed along the washes in the swales. |
| | |
| | |
| | |
| | |
| | |
| | |
| b. 0th | er Surface Use Activities: The surface is Federally owned and |
| managed | by the BLM/USGS. |
| | |
| | • · · · · · · · · · · · · · · · · · · · |
| | |
| c. Pro | |
| | ximity of Water, Dwelling, Historical Sites: |
| 1.1 | ximity of Water, Dwelling, Historical Sites: Water: None known |
| 1: | Water : None known |
| 2. | Water: None known Dwellings: None |
| | Water: None known Dwellings: None Historical sites: An Archaeological Cultural Resource Survey was |
| 2. | Water: None known Dwellings: None Historical sites: An Archaeological Cultural Resource Survey was conducted for this location. The report dated February 2, 1981, is |
| 2. | Water: None known Dwellings: None Historical sites: An Archaeological Cultural Resource Survey was |
| 2. | Water: None known Dwellings: None Historical sites: An Archaeological Cultural Resource Survey was conducted for this location. The report dated February 2, 1981, is |
| 2. | Water: None known Dwellings: None Historical sites: An Archaeological Cultural Resource Survey was conducted for this location. The report dated February 2, 1981, is |

12. Operator's Representative


| Field Personnel who can be contact | ed concerning compliance of this Surface |
|------------------------------------|--|
| Use Plan are as follows: | |
| Zeus Energy, Inc. | Rocky Mountain Petroleum Consultants, Inc. |
| Robert C. Taylor | Thomas E. Wolter |
| 268 South Main Street | 136 South Main St., Suite 822 |
| Salt Lake City, Utah 84101 | Salt Lake City, Utah 84101 |
| Office: 801/531-6764 | Office: 801/328-3017 |
| | Home: 801/363-1462 |


13. Certification

I hereby certify that I, or persons under my direct supervision, have inspected the proposed drill site and access route; that I am familiar with the conditions as they actually exist; that the statements made in this plan are, to the best of my knowledge, true and correct; and that the proposed work performed by Zeus Energy, Inc. and its contractors and sub-contractors will conform to this plan.

DATE: May 18, 1981

Robert C Taylor








SCALE : 1" = 60'

Zeus Energy, Inc. Federal 1-9 (proposed) Section 9, T 14 S, R 19 W Juab County, Utah

PRODUCTION FACILITIES EXHIBIT III





SCALE : 1 = 60'

Zeus Energy, Inc.

Federal 1-9 (proposed) Section 9, T 14 S, R 19 W Juab County, Utah

RIG LAYOUT

EXHIBIT IV







February 2, 1981

Robert Taylor Zeus Energy 268 South Main Street Salt Lake City, Utah 84101

Dear Mr. Taylor,

Enclosed is the final report and billing for our cultural resource survey of two drill locations in Juab County, Utah. Copies of the report have been distributed to the appropriate government agencies.

If you have any questions concerning the report or our billing, please don't hesitate to call.

Sincerely,

Richard N. Holmer

Research Assistant Professor

at

Copies sent to:
Richard Fike, State Archeologist
Bureau of Land Management
Dr. David Madsen
Utah Historical Society
Antiquities Section
Craig Harmon
Bureau of Land Management
Richfield, Utah

A CULTURAL RESOURCE SURVEY OF TWO DRILL LOCATIONS IN JUAB COUNTY, UTAH

Ву

Steven R. Simms

ARCHEOLOGICAL CENTER
DEPARTMENT OF ANTHROPOLOGY
UNIVERSITY OF UTAH

Prepared for

Zeus Energy, Inc.

REPORTS OF ENVESTIGATIONS 81-3

January 1981

Utah State Antiquities Section Permit Number 570

Department of Interior Permit Number 81-UT-044

ABSTRACT

An archeological survey was conducted on two proposed drill sites in Juab County, Utah for historic and prehistoric cultural resources. It was determined from the field investigations and records search that no cultural resources will be adversely affected by the drilling activities.

INTRODUCTION

This report is submitted in partial fulfillment of an agreement between the University of Utah Archeological Center and Zeus Energy, Inc. of Salt Lake City, for the survey of the historic and prehistoric cultural resources on two proposed drill sites near the south end of the Deep Creek Mountains in western Utah. The two drill sites are located on land administered by the Bureau of Land Management, Richfield District. The survey was conducted by Steven Simms of the University of Utah on January 23, 1981.

SETTING AND LOCATION

The survey area is located in Pleasant Valley Draw which drains into Snake Valley from the southern end of the Deep Creek Mountains. The survey area is situated on two low swells at the toe of a broad alluvial fan. These swells are composed of gravel deposits and are deflating indicating the surface is relatively old by archeological measures. The two drill locations are approximately 100 meters apart at an elevation of 1333: meters (5400 feet).

The vegetation of the survey area is sparse, consisting of annuals and grasses interspersed with occasional saltbrush (Atriplex spp.) on the low swells with sagebrush (Artemisia tridentata), rabbitbrush (Chrysothamus spp.), and snakeweed (Gutierrezia microcephala) along the washes in the swales.

LITERATURE AND RECORDS SEARCH

Prior to the initiation of the field examination, a record search was conducted of the archeological and historical files at the University of Utah and the Antiquities Section, Utah State Historical Society. There are no sites of a historic or prehistoric nature that have been recorded on or near the survey area. There are no sites listed on the National Register of Historic Places, or nominated to the Register in the immediated vicinity of the survey area.

SURVEY PROCEDURES

Access to the drill sites was via dirt roads leading north from U.S. highway 50 at the Utah-Nevada state line. The drill sites were marked by surveyor's flagging and stakes. The drill sites were examined by walking the area from the road to a point 100 meters west of each location and to points 50 meters north and scuth of each location. By surveying a single block between the locations and the road, the placement of the access road to the locations can be flexible. Soil and vegetation characteristics were noted.


DESCRIPTION OF DRILL SITES


The proposed drill sites are located 41 road miles north of U.S. highway 50 in Pleasant Valley Draw. Both locations are in the NE 1/4 of the SW 1/4 of the SE 1/4 of section 9, T14S; R19W. The existing road comes to within 200 meters of the proposed locations. From there, an access road will be constructed.

SURVEY RESULTS AND RECOMMENDATIONS


The intensive examination of two drill sites and the area between the drill sites and the nearest access road revealed no cultural remains of either a historic or prehistoric nature with the exception of a cut wood fragment and a white enamel plate. These artifacts are of no archeological significance. Neither were there any previously recorded sites in the survey area. Therefore, no cultural resources will be endangered by the proposed drilling activities. Additionally, the probability of subsurface archeological remains is low. However, if subsurface archeological material is encountered during location preparation, all work should halt immediately and an archeologist be informed.







Surveyed drill sites in Juab County, Utah. From U.S.G.S. Trout Creek Quadrangle - 15' series (topographic) Survey area (both locations are within this block)





DISTRIBUTION LIST

Contractor:

Zeus Energy, Inc. 268 South Main Street Salt Lake City, Utah 84101

Attn. Robert Taylor

Land Ownership

Richard Fike Bureau of Land Management University Club Building 136 E. South Temple Salt Lake City, Utah 84111

Craig Harmon
Bureau of Land Management
Richfield District
150 E. 980 North
Richfield, Utah 84701

State Agency

David B. Madsen Antiquities Section Utah State Historical Society 300 Rio Grande Room 210 Salt Lake City, Utah 84101

UNITED STATES DEPARTMENT OF THE INTERIOR

| | DEI AIT I MEIT | 5 LEANE DENIGNATION AND BERIAL NO. | | | | | | | | |
|--|--|------------------------------------|--------------------------------|-----------|------------------|-------------------------------|--|--|--|--|
| GEOLOGICAL SURVEY | | | | | | | U-40560 A | | | |
| APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK | | | | | | | 6. IF INDIAN, ALLOTTES OR TRIBE NAME | | | |
| 1a. TYPE OF WORK DRI | | 7. UNIT AGREEMENT NAME | | | | | | | | |
| WELL W | AS OTHER | | 81N 201 | GLE X | MULTIPE ZONE | • 🗆 | S. FARM OR LEASE NAME | | | |
| 2. NAME OF OPERATOR | | | | | | | Federal | | | |
| Zeus Energy, Inc. | | | | | | | 9. WELL NO. | | | |
| ADDRESS OF OPERATOR | | | | | | | 1-9 | | | |
| 268 South | Main St., Sali | | 10. FIELD AND POOL, OR WILDCAT | | | | | | | |
| 4. LOCATION OF WELL (R | . LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*) | | | | | | | | | |
| At proposed prod. zone At proposed prod. zone At proposed prod. zone | | | | | | | 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 9, T-14-S, R-19-W | | | |
| Same a | Same as above SW2, NW2, SF2 24/2 FEL 4. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE. | | | | | | | | | |
| 14. DISTANCE IN MILES | 4. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE | | | | | | 12. COUNTY OR PARISH 13. STATE | | | |
| 45 miles northwest of Delta. Utah | | | | | | Jua b Utah | | | | |
| 15. DISTANCE FROM PROPOSED [®] 16. NO. OF ACRES IN LEASE 17. NO. (| | | | | | OF ACRES ASSIGNED HIS WELL | | | | |
| PROPERTY OR LEASE LINE, FT. (Also to nearest drig, unit line, if any) 1360.5 | | | | | | 40 | | | | |
| 18. DISTANCE FROM PROPOSED LOCATION 19. PROPOSED DEPTH 20. ROTA | | | | | | RY OR CABLE TOOLS | | | | |
| TO NEAREST WELL, DRILLING, COMPLETED, OR APPLIED FOR, ON THIS LEASE, FT. N/A 5000' | | | | | tary | | | | | |
| 21. ELEVATIONS (Show wh | ether DF, RT, GR, etc.) | | | | | | 22. APPROX. DATE WORK WILL START | | | |
| 5400' GR | | | | | | | June 20. 1981 | | | |
| 23. | F | PROPOSED CASING | AND | CEMENTING | PROGRA | M | | | | |
| SIZE OF HOLE | SIZE OF CASING | WEIGHT PER FOO | OOT SETTING DEPTH | | | QUANTITY OF CEMENT | | | | |
| 12¼" | 8 5/8" | 36#/ft; | 500 | | Circ. to surface | | | | | |
| 7 7/8" | 414" | 10.5#/ft | | | | | determined by logs | | | |
| | ĺ | | 1 | | ŀ | | | | | |

RECEIVED
MAR 25 1982

DIVISION OF OIL, GAS & MINING

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen or plug back, give data on present productive zone and proposed new productive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program, if any.

| preventer program, it any. | | * |
|--|--|--------------|
| signed Robert. C. Taylor | President | DATE 5/18/81 |
| (This space for Federal or State office use) | | |
| APPROVED BY Imad Calland | E. W. Guynn TITLE District Oil & Gas Supervisor | MAR 2 4 1982 |
| CONDITIONS OF ATTROVAL, IF ANY: | | |

NOTICE OF APPROVAL

*See Instructions On Reverse Side
CONDITIONS OF APPROVAL ATTACHED
TO OPERATOR'S COPY

FLARING OR VENTING OF GAS IS SUBJECT TO NTL 4-DATED 1/1/80 United States Department of the Interior
Geological Survey
Oil and Gas Operations
2000 Administration Building
1745 West 1700 South
Salt Lake City, Utah 84104

NEPA CATEGORICAL EXCLUSION REVIEW

| PROJECT IDENTIFICAT | ION | |
|----------------------------------|--|---------------------------|
| Operator/Project Na | me Zeus ENERGY INC. | WELL No 1-9 |
| Project Type Oil | · | |
| Project Location 13 | 360' FSL, 2412' FEL, SEC 9 | T145 R19W |
| Date Project Submit | ted 5-26-81 | |
| FIELD INSPECTION | Date | |
| Field Inspection Participants | BIERRY HIRSCHI | BLM |
| | DENNIS MARCIN | BLM |
| e v | ROBERT TAYLOR | ZEUS |
| | JIM KEOGH | KEDGH TAX. |
| | TOM TACKETT | TKrOTIK |
| | | , 69 |
| • | • | |
| review quidelines. | e proposal in accordance with the This proposal would not involve es not represent an exception to | e any significant effects |
| , / | 00 | |

I concur

JUN 3 0 1981

Date

W Monther FOR

E. W. GUYNN DISTRICT ENGINEER

District Supervisor

CATEGORICAL EXCLUSION REVIEW INFORMATION SOURCE

| Criteria 516 DM 2.3.A | Corre- spondence (date) | ral/State Age Phone check (date) | ency Meeting (date) | Local and private correspondence (date) | Previous NEPA | Other studies and reports | Staff expertise | Onsite inspection (date) | Other |
|--|-------------------------------|---|---------------------------|---|------------------|------------------------------------|--------------------|--------------------------------|-------|
| . Public health) safety | 1 (6-24-81) | | | | | 2 | 6 | | 4,8 |
| . Unique characteristics | 1. | 9(6-30-81) (6-22-81) | , | À | \$ g | 2 , | | | 4,8 |
| Environmentally controversial | ĺ | 9 (6-22-81) | | | | | 6 | | 4 |
| . Uncertain and unknown risks | 1 | 9 (6-30-81) | | : : | | 2 | - | | 4,8 |
| Establishes precedents | 1 | | : | | | | | | 4,8 |
| 6. Cumulatively gnificant | | | | : | | | | | 4 |
| 7. National Register historic places | | 9 (6-29-81) | | | | , | | , | 4 |
| 8. Endangered/ threatened species | | 9 (6-29-81) | - - - - - | | | 1 | | | |
| 9. Violate Federal, State, local, tribal law | | | · | | | | 6 | | 4,8 |

SEE ATTAICHED LEGEND

CATEGORICAL EXCLUSION REVIEW COMMON REFERENCE LEGEND

- 1. Surface Management Agency Input
- 2. Reviews Reports, or information received from Geological Survey (Conservation Division, Geological Division, Water Resource Division, Topographic Division)
- 3. Lease Stipulations/Terms
- 4. Application Permit to Drill
- 5. Operator Correspondence
- 6. Field Observation
- 7. Private Rehabilitation Agreement
- 8. RECOMMENDED STIPULATIONS
- 9. MEMORANDA TO WELL File DOCUMENTING TELECONS.
 and MEETINGS

RECOMMENDED STIPULATIONS

- 1. ALL FRESH WATER HORIZONS SHALL BE PROTECTED BY ISOLATING WITH CEMENT.
- 2, THE DEPTH OF ANY ABNORMALLY HIGH TEMPERATURES SHALL BE REFORTED TO DEFINE POTENTIAL GEOTHERMAL RESOURCES
- 3. THE ACCESS ROAD TO THE LOCATION WILL FOLLOW THE LARGE FLAT WASH WEST OF THE WELLSITE
- 4. THE DRILL PAD WILL BE ROTATED 90° Counterclockwise, with sesence pits on the west side of the waston. Pod dimentions will be sestricted to zooft east-west by 300 ft. north-South.
- S. THERESERVE PIT SHALL BE ALLOWED TO PRY PRIOR TO BACK-FILLING AND MATERIALS BURIED MUST BE COVERED WITH AT LEAST FOUR FEET DE SOIL.
- 61 THE TOP 6 INCHES OF TOPSOIL SHALL BE STOCKPILED FROM THE PAD SITE AND NEW ACCESS END FOR REDISTRIBUTION DURING REHABILITATION:
- 1. THE FOLLOWING SEED MIXTURE WILL BE USED TO RESSEED THE ROAD AND PAD AREA:

YEILOW SWEET CLOVER 3 lbs/acre SHADSCALE 3 lbs/acre WINTERFAT 2 lbs/acre Crested WHEATGRASS 3 lbs/acre

SPEDING SHALL BE DONE AFTER OCTOBER 15.

8, THE BUREAU OF LAND MANAGEMENT SHALL BE INFORMED OF REHABILITATION AND SEEDING OPERATION DATES SO A REPRESENTATIVE CAN BE PRESENT

- Sing



United States Department of the Interior

IN REPLY REFER TO 2064

U-056

BUREAU OF LAND MANAGEMENT HOUSE RANGE RESOURCE AREA Fillmore, Utah 84631

June 24, 1981

Geological Survey Conservation Division 2000 Administration Building 1745 West 1700 South Salt Lake City, Utah 84138

Gentlemen:

Attached is a Staff Report for the inspection of the Zeus Energy Inc. oil well site in T. 14 S., R. 19 W., Section 9.

Please use the recommendation in the Staff Report for the issuing of the drilling permit.

The Bureau of Land Management representative who will be available for consultation during construction and rehabilitation activities is Birrell Hirschi, House Range Resource Area, P. O. Box 778, Fillmore, Utah 84631, office phone 743-6811, home phone 743-5172.

Sincerely yours,

Area Manager

Enclosure Staff Report



United States Department of the Interior

3100 U-056

BUREAU OF LAND MANAGEMENT HOUSE RANGE RESOURCE AREA Fillmore, Utah 84631

STAFF REPORT

TITLE: Well Site Investigation, U.S.G.S., BLM and Zeus Energy Inc.

DATE: June 22, 1981

AUTHOR: Birrell Hirschi, Surface Protection Specialist

On June 17, 1981 I received a telephone call from George Diwachak at home at 7:00 a.m. George said he had been involved in an auto accident and would not be able to attend the on site inspection with Zeus Energy Inc. site in Pleasant Valley and asked if I would fill in for him and advise him back.

One June 17, 1981 at 11:30 am Birrell Hirschi and Dennis Marcin met Robert C. Taylor (Zeus Energy Inc.), Jim Keogh (Keogh Inc.) and Tom Tackett (Tackett Inc.) at the well site.

The site location was on the south drainage slope of Pleasant Valley south of the road and between two large flat washes. The vegetation consisted of galleta grass, desert globemallow, broom snakeweed, little-leaf horsebrush, winterfat, evening primrose, Nevada mormon tea, shadscale, greasewood, hoary aster and mustard.

The drill site will be a 200' x 300' site. The 200' distance will be east and west while the 300' will be north and south. The sludge pits will be on the swith end of the pad at the head of a short wash that starts on the pad site.

The road to the drill pad will be up the large flat wash adjacent to the site to the west.

It is recommended that the top 6" of soil be stockpiled for redistribution over the drill site when it is rehabilitated. That the road and the disturbed areas be reseeded using the following mixture.

Yellow sweet clover 3 lbs/acre Shadscale 3 lbs/acre Winter fat 2 lbs/acre Crested wheatgrass 3 lbs/acre

The USGS should be informed that the operator be required to inform the BLM when the rehabilitation is to take place and that the seeding be done after the 15th of October, and that a BLM representative be present when this is done.

E. Blis Hunda

| A Company of the contract of t |
|--|
| FROM: DISTRICT GEOLOGIST, SALT LAKE CITY, UTAH O : DISTRICT ENGINEER, O&G, SALT LAKE CITY, UTAH SUBJECT: APD MINERAL EVALUATION REPORT OPERATOR: Zeus Energy I=nc. Well No. 1-9 |
| LOCATION: SEX NEXSWX sec. 9, T. 145, R. 19W, SLBOM Juab county, Utah |
| 1. Stratigraphy: Quaternary Aluvium - Surf (5400'GR) Tertiary - Luke Sediments -? TD - 5000' in? Paleozoic or Niesozoic rocks may be |
| drilled at lower drilling depths. 2. Fresh Water: Fresh to useable water should |
| cocur to T.D. (5000') in Tertiary formations. 3. Leasable Minerals: prospect lies within the |
| Gandy spras. Geothermal prospectively valuable resource area. Six wells and Surface spring in Snake Valley show temperatures ranging from 200-27°C, and have flow rates up to 17000 Liters/min. |
| 4. Additional Logs Needed: |
| none |
| 5. Potential Geologic Hazards: None known. an elevated geothermal gradient may be encountered. 5. References and Remarks: |

WRD (C-20-19)25 UG+M5-Geothermal Resources of Utah (Map) Signature: Stury Shrili Date: 6-4-81

Scott M. Matheson, Governor Temple A. Reynolds, Executive Director Cleon B. Feight, Division Director

4241 State Office Building • Salt Lake City, UT 84114 • 801-533-5771

May 6, 1982

Zues Energy, Inc. 268 South Main Street Salt Lake City, Utah 84101

Re: Well No. Federal #1-9
Sec. 9, T. 14S, R. 19W.
Juab County, Utah

Gentlemen:

In reference to the above mentioned wells, considerable time has gone by since approval was obtained from this office.

This office has not received any notification of spudding. If you do not intend to drill these wells, please notify this Division. If spudding or any other activity has taken place, please send necessary forms. If you plan to drill this location at a later date, please notify as such.

Your prompt attention to the above will be greatly appreciated.

Very truly yours,

DIVISION OF OIL, GAS AND MINING

Cari Furse Clerk Typist

ZEUS ENERGY INC.

268 South Main
Salt Lake City, Utah 84101
(801) 531-1817

May 10, 1982

State of Utah Natural Resources & Energy Oil, Gas & Mining 4241 State Office Building Salt Lake City, Utah 84114

> Re: Well No. Federal No. 1-9 Sec. 9, T. 14S, R. 19W Juab County, Utah

Gentlemen:

Reference your letter of May 6, 1982, with regard to the above-referenced drilling permit issued March, 1982, it is our intention to spud in sometime this summer. You office will be notified fifteen (15) days prior to the date we spud in as outlined in the drilling permit.

If I may be of any further assistance, please do not hesitate to call.

Very truly yours,

obert C. Taylor

President

RCT/prb

REGERVED)
MAY 1 1 1982

DIVISION OF OIL, GAS & MINING



4241 State Office Building • Salt Lake City, UT 84114 • 301-533-5771

March 17, 1983

Zeus Energy, Inc. 268 South Main Salt Lake City, Utah 84101

> Re: Well No. Federal # 1-9 Sec. 9, T. 14S, R. 19W. Juab County, Utah

Gentlemen:

In reference to the above mentioned well, considerable time has gone by since approval was obtained from this office.

This office has not received any notification of spudding. If you do not intend to drill this well, please notify this Division. If spudding or any other activity has taken place, please send necessary forms. If you plan to drill this location at a later date, please notify as such.

We will be happy to acknowledge receipt of your response to this notice if you will include an extra copy of the transmittal letter with a place for our signature, and a self addressed envelope for the return. Such acknowledgement should avoid unnecessary mailing of a firm second notice from our agency.

Your prompt attention to the above will be greatly appreciated.

Respectfully,

DIVISION OF OIL, GAS AND MINING

Cari Furse

Well Records Specialist

CF/cf

March 21, 1983

RE: Well No. Federal #1-9 Sec. 9, T14S, R19W Juab County, Utah

State of Utah
Natural Resources & Energy
Division of Oil, Gas and Mining
4241 State Office Building
Salt Lake City, Utah 84114

Attention: Cari Furse

Well Records Specialist

Gentlemen:

In answer to your letter dated March 17, 1983, we intend to drill on the above-mentioned well at a later date. We are awaiting funding at this time and will inform your office when funding becomes available.

We are enclosing a copy of this letter to be returned as an acknowledgement of receipt and a self-addressed envelope.

Thank you.

Very truly yours,

ZEUS ENERGY, INC.

Robert C. Taylo

/cas Enclosures

Acknowledgement of Receipt

DIVISION OF OU GAS & MINING

MAR 2 3 1983

State of Utah, Division of Oil, Gas and Mining

DATE

Oil and Cas Operations 2000 Administration Building 1745 West 1700 South Salt Lake City, Utah 84104

April 4, 1983

Zeus Energy, Inc 268 South Main Street Salt Lake City, Utah 84101

> Re: Rescind Application for Permit to Drill Well No. 1-9 Section 9, T. 14 S., R. 19 W. Juab County, Utah Lease U-40560-A

Gentlemen:

The Application for Permit to Drill the referenced well was approved on March 24, 1982. Since that date no known activity has transpired at the approved location. Under District policy, applications for permit to drill are effective for a period of one year. In view of the foregoing this office is rescinding the approval of the referenced application without prejudice. If you intend to drill at this location at a future date, a new application for permit to drill must be submitted.

This office requires a letter confirming that no surface disturbance has been made for this drill site. Any surface disturbance associated with the approved location of the well will be rehabilitated. A schedule for this rehabilitation must then be submitted to this office. Your cooperation in this matter is appreciated.

Sincerely,

(ORIG. SGD.) W. P. MARTEMS Drilling Unit Supervisor

E. W. Guynn
District Oil and Gas Supervisor

bcc: Well File
SMA
State O&G
State BLM
APD Control
Vernal or Durango

WPM/kr



4241 State Office Building • Salt Lake City, UT 84114 • 8(11-533-5771

April 7, 1983

Zeus Energy, Inc. 268 South Main Street Salt Lake City, Utah 84101

RE: Rescind Application for

Permit to Drill Well No. 1-9

Sec. 9, T.14S, R.19W Juab County, Utah

Gentlemen:

Approval of Application for Permit to Drill the above referenced well is rescinded without prejudice as of the above date in concert with action taken by Oil and Gas Operations.

If you intend to drill this location at a future date, a new application for permit to drill may be submitted for State approval.

Sincerely.

Norman C. Stout

Administrative Assistant

NS/as